



TECHNICAL SPECIFICATION

P.A. SYSTEM SPECIFICATION

2x MARTIN 15" FOH Speakers

2x CROWN XTi1000 FOH Amplifiers

1x MARTIN 18" Sub Speaker

1x CROWN XTi2000 Sub Amplifier

4x TURBOSOUND 12" Foldback Monitor Speakers

2x CROWN XTi1000 Foldback Amplifier

4x BEHRINGER DI Boxes

2x STAGG Stereo DI Boxes

YAMAHA LS9 16 on 16 Channel Digital Mixing Console

STAGE: 4m x 2.5m with a total floor area of 10m² lit with 5 PAR can stage lights. Projection facilities available onto a 2m x 2m screen to rear of stage. Connection via 9pin VGA/DVI cable between PC/Mac laptop and projector.

STANDING AUDIENCE CAPACITY: 70



MICROPHONE LIST

- 4x SHURE SM58 Cardioid Dynamic Microphones
- 2x SHURE SM57 Cardioid Dynamic Microphone
- 1x SHURE BETA 57a Super-Cardioid Dynamic Microphone
- 1x ELECTROVOICE ND767 Super-Cardioid Dynamic Microphone
- 2x SENNHEISER e606 Microphone
- 1x AKG D112 Kick Drum Microphone
- 1x AUDIX D6 Kick Drum Microphone
- 2x AUDIX D2 Rack Tom Microphone
- 1x AUDIX D4 Floor Tom Microphone
- 1x AUDIX i5 Snare Microphone
- 2x RODE NT5 Condenser Microphone (Matched Pair)
- 1x RODE M3 Condenser Microphone
- 2x SE ELECTRONICS SE1A Condenser Microphone (Matched Pair)